1997 Mazda MX-5 Miata

1997-98 MANUAL TRANSMISSION SERVICING Mazda

1997-98 MANUAL TRANSMISSION SERVICING

Mazda

APPLICATION

TRANSMISSION APPLICATIONS

Vehicle Application	Transmission/Transaxle Model
B2300, B2500, B3000 & B4000	M50D-R1
Miata	M15M-D
MX-6 & 626	G25M-R
Protege	F25M-R

NOTE: Mazda B2300, B2500, B3000 and B4000 are referred to as B-Series throughout

this article.

LUBRICATION

SERVICE INTERVALS

Fluid Inspection & Replacement

Check fluid level(s) at least once a year. Change transmission/transaxle and transfer case fluids every 60,000 miles for normal driving conditions and every 30,000 miles for severe driving conditions.

CHECKING FLUID LEVEL

Transaxle Fluid

Remove fill plug from transaxle. Fluid should be up to bottom of fill hole on side of case.

Transmission Fluid (RWD Models)

Remove fill plug from transmission. Fluid should be up to bottom of fill hole on side of case.

Transfer Case Fluid (4WD)

Remove fill plug from transfer case. Fluid should be up to bottom of fill hole on side of transfer case.

RECOMMENDED FLUID

FLUID SPECIFICATIONS

Application	Recommended Fluid
Transmission	

1997 Mazda MX-5 Miata

1997-98 MANUAL TRANSMISSION SERVICING Mazda

B-Series	MERCON Or M-III ATF
All Other Models	
All-Season Usage	⁽¹⁾ SAE 75W-90
Temp. Greater Than 50°F (10°C)	⁽¹⁾ SAE 80W-90
Transfer Case	·
B-Series	Dexron-II Or MERCON
	ATF
(1) API GL-4 or GL-5.	

FLUID CAPACITIES

TRANSMISSION/TRANSAXLE REFILL CAPACITIES

Application	Qts. (L)
B-Series	2.8 (2.6)
Miata	2.1 (2.0)
MX-6 & 626	2.9 (2.7)
Protege	2.9 (2.7)

TRANSFER CASE REFILL CAPACITY

Application	Qts. (L)
B-Series	1.3 (1.2)

ADJUSTMENTS

GEARSHIFT LINKAGE

No external linkage adjustment is required.

TORQUE SPECIFICATIONS

TORQUE SPECIFICATIONS

Application	Ft. Lbs. (N.m)
Drain Plug ⁽¹⁾	
B-Series	30-43 (40-58)
Miata, MX-6, Protege & 626	30-43 (40-58)
Fill Plug	
B-Series	30-43 (40-58)
Miata	18-29 (24-39)
MX-6, Protege & 626	30-43 (40-58)
Transfer Case Plug (B-Series)	14-22 (19-30)

1997 Mazda MX-5 Miata

1997-98 MANUAL TRANSMISSION SERVICING Mazda

	INCH Lbs. (N.m)
Speedometer Gear Bolt (FWD)	69-95 (8-11)
(1) Install NEW washer.	